

# Shelf Life

The shelf life of Vycor® Self-Adhered Flashings (Vycor® Plus, Vycor® V40, Vycor® Aluminum, Vycor® PRO and Vycor® Deck Protector) is highly dependent on storage conditions. In general, these products should be stored in their original, unopened packaging at ambient temperatures between 40–90°F (5–32°C) under dry conditions and protected from exposure to direct sunlight.

Vycor® Self-Adhered Flashings should be used within one year from the date of manufacture.

[gcpat.com](http://gcpat.com) | North America Customer Service: 1-866-333-3726

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

Vycor and Vycor Deck Protector are trademarks, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2016 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140 USA.

In Canada, GCP Canada, Inc., 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6.

Printed in U.S.A. TP-065-0416 RE0071 CD/PDF