

TRIOject

Product Application

• Sealing of construction joints, cold joints and working joints in concrete, where reinjection may be necessary.

Product Advantages

- Three independent injection channels
- Pressure activated apertures
- Durable construction
- Wire mesh for additional protection
- Foam pad adapts to irregular surface

Grouts

There are various grouts available depending on site conditions and other requirements. Contact your local sales representative or technical service consultant for the grout best used in the application.

Properties

Typical Properties

Width	1 1/8 inch
Height	5/8 inch
Channel diameter	1/4 inch

Installation Guidelines

Procedure for the installation

Place TRIOject in the middle of the construction joint. With thick structural sections, greater than 20 inches, place TRIOject about 10 inches away from the external water side.

If two runs of TRIOject are used, the hoses should be at least 2 inches apart. The length of each run of hose should not exceed 26 ft.

Ensure continuous contact with joint by fastening the TRIOject mesh with nails at 1 ft. intervals.

After the concrete has cured 28 days, the first channel can be injected with Superflex AR acrylate grout.



Packaging & Handling

TRIOject is packaged in rolls of 328 ft., 1 roll per case, 25 lbs. per case.

TRIOject wire mesh is supplied in a pack containing 50 pieces, each 3.27 ft. long, for total of 164 ft. per pack. Two packs of wire mesh are needed per case of TRIOject Injection Hose.

TRIOject should be stored under cover, clear of the ground. Protect the materials from all sources of moisture and frost. Shelf life is unlimited.

Health and Safety

Always use protective clothing, gloves and goggles consistent with OSHA regulations during use. Avoid eye and skin contact. Do not ingest. Refer to Safety Data Sheet (SDS) for detailed safety precautions. SDS's can be obtained from GCP Applied Technologies or from our web site at gcpat.com.

Limitations

TRIOject must be installed using the TRIOject wire mesh and Vario Packers for proper placement and injection(s).

ca.qcpat.com | North America customer service: 1-877-4AD-MIX (1-877-423-6491)

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

TRIOject is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2018 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140 USA.

In Canada, GCP Canada, Inc., 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6.

This document is only current as of the last updated date stated below and is valid only for use in the Canada. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.qcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.