

QUANTEC[®] XL-524P

Set accelerating plasticizer

Product Description

QUANTEC[®]XL-524P admixture is a non-chloride based plasticizing set accelerator for machine produced concrete products where the process requires zero or very low slump concrete.

Product Advantages

- Hastens hydration process
- Increased throughput
- Better compaction
- Increased plasticity
- Reduced cracking and crazing
- Sharper corners and edges
- Fewer culls

Product Uses

QUANTEC[®]XL-524P admixture may be used in all zero or low slump concrete to increase workability while retaining cohesiveness and providing more rapid hydration of the cement. In addition, the admixture gives the acceleration necessary to provide early strength while reducing or eliminating the requirement for steam curing. This benefit can also allow for replacement of Type III Cement with Type I Cement.

QUANTEC[®]XL-524P admixture is intended for use in concrete block mixes and may be beneficially used in concrete pavers and segmental retaining wall units. QUANTEC[®]XL-524P admixture is both a dispersing agent as well as an accelerating admixture. By dispersing the cement and aggregate fines, it improves the workability of the mix. Dispersion of the cement results in more complete hydration. This, coupled with the acceleration produced by QUANTEC[®]XL-524P admixture, provide greater early strength for any given cement content.

The increased workability provided by the admixture allows for better compaction with less cracking and crazing, sharper corners and edges, resulting in fewer culls. Production can be increased, absorption reduced and appearance and texture greatly improved.

Application Information

Addition Rates

QUANTEC[®]XL-524P admixture is used at a rate of 6-10 oz/cwt (390-650 mL/100 kg) of cementitious materials, including pozzolans. The addition rate is dependent upon the specific set of materials and the desired end properties.

Packaging

QUANTEC®XL-524P admixture is available in drums and returnable totes.

Health & Safety

All precautions defined on the SDS (Safety Data Sheet) for QUANTEC®XL-524P admixture must be followed.

Storage

QUANTEC®XL-524P admixture will begin to freeze at approximately 32°F (0°C), but will return to full strength after thawing and thorough mechanical agitation.

ca.gcpat.com | North America customer service: 1-877-4AD-MIX (1-877-423-6491)

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

QUANTEC is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2018 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140 USA.

In Canada, 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6.

Ce document est à jour seulement à la date de la dernière mise à jour indiquée ci-dessous et n'est valide que pour une utilisation au Canada. Il est important que vous consultiez toujours les informations actuellement disponibles sur l'URL ci-dessous pour fournir les informations les plus récentes sur le produit au moment de l'utilisation. Des documents supplémentaires tels que les manuels de l'entrepreneur, les bulletins techniques, les dessins détaillés et les recommandations détaillées ainsi que d'autres documents pertinents sont également disponibles sur www.ca.gcpat.com. Les informations trouvées sur d'autres sites Web ne doivent pas être utilisées, car elles peuvent ne pas être à jour ou applicables aux conditions de votre site et nous déclinons toute responsabilité quant à leur contenu. S'il y a des conflits ou si vous avez besoin de plus d'informations, veuillez contacter le service client de GCP.

Last Updated: 2018-12-12

ca.gcpat.com/solutions/products/masonry-hardscape-solutions/quantec-xl-524p