

The DRY-BLOCK® System

DRY-BLOCK® is a system specially designed to provide concrete masonry structures with outstanding water-repellent characteristics. The DRY-BLOCK System consists of two separate admixtures. DRY-BLOCK Block Admixture is mixed throughout the concrete during manufacture of the concrete masonry units and DRY-BLOCK Mortar Admixture is added to the mortar. To complement DRY-BLOCK admixtures, INFINISEAL™ DB, a water-based, clear penetrating sealer, can be field applied to provide maximum protection to the masonry wall.

DRY-BLOCK® Block and Mortar Admixtures are chemically different and are NOT interchangeable. The differences between concrete block and mortar are extensive and a well-engineered admixture system will address the requirements of each wall component separately by providing a unique formulation for each.

On one hand, concrete block is manufactured with low-slump concrete using relatively low cement to aggregate ratios, a wide variety of aggregates, a relatively small amount of water and special curing conditions. DRY-BLOCK® Block Admixture is formulated for use in concrete masonry units and provides the block producer with a single, easy to use product that imparts water-repellency. DRY-BLOCK Block Admixture also provides other useful benefits to manufactured low-slump concrete, like improved compressive strength and absorption properties, as well as improved “machinability” or ease of manufacturing units.

Mortar, on the other hand, is produced to a more fluid consistency with higher cement to aggregate ratios, a finer aggregate, greater amounts of water and curing under open air conditions. Taking these characteristics into account, DRY-BLOCK® Mortar Admixture is formulated to provide water-repellency and workability to the mortar. It is specifically formulated to work with concrete masonry units containing DRY-BLOCK Block Admixture. This combination provides a wall system with water-repellent properties able to meet and exceed the most stringent industry standards.

When a DRY-BLOCK® water-repellent wall system is desired, both the block and mortar admixtures must be used. Elimination of either component will compromise the integrity of the water-repellent properties of the masonry structure and is not allowed by the DRY-BLOCK specification.

DRY-BLOCK® Block and Mortar admixtures have successfully performed as a standalone system for years. But, if a “belt and suspenders” system is desired, then field apply INFINISEAL™ DB Sealer, a water-based, clear, penetrating water-repellent sealer to the exterior of the wall. INFINISEAL DB complements DRY-BLOCK admixtures and provides maximum protection to the masonry wall. INFINISEAL DB has been specially formulated to work with both new and existing DRY-BLOCK structures.

DRY-BLOCK® is a system engineered to impart superior water-repellent properties to concrete masonry assemblies. Each admixture is designed to provide the necessary properties to both the block and mortar so that the resultant wall offers a high level of performance. DRY-BLOCK Admixtures have achieved more than 30 years of success in creating superior masonry structures. The application of INFINISEAL™ DB provides another level of protection. The DRY-BLOCK Admixtures used in conjunction with INFINISEAL DB provide a unique system of water-repellency.

gcpat.com | North American Customer Service: 1-877-423-6491

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

Strux is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2016 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140 USA.

In Canada, 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6.

GCP0083 STRUX-46-1016

