

Printing date 01/19/2023

Safety Data Sheet

Version Number 1.0

Reviewed on 01/19/2023

Page 1/9

1 Identification

Product identifier

Trade name: MK 6-HY

SDS ID Number: 2684

Relevant identified uses of the substance or mixture, and uses advised against: Specialty construction product. Not intended for other uses.

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

GCP Applied Technologies 2325 Lakeview Pkwy Alpharetta GA 30009 USA

GCP Canada, Inc. 294 Clements Road W. Ajax, Ontario L1S 3C6 Canada

Information department:

Environmental Health & Safety USA: +1-617-876-1400 (24 hours) +1-800-354-5414 (8AM - 5PM) Not functional within Massachusetts CAN: 1-905-683-8561 (24 hours) Email address: msds.gcp@gcpat.com email: msds.gcp@gcpat.com

Transport Emergency: Chemtrec +1-800-424-9300 (24 hours)

2 Hazard(s) identification

Classification of the substance or mixture

Depending on the type of handling and use, airborne respirable crystalline silica may be generated. Prolonged and/or massive inhalation of respirable silica dust may cause silicosis. Occupational exposure to respirable crystalline silica should be monitored and controlled.

This product should be handled with care to avoid dust generation.

May cause cancer. Route of exposure: Inhalation.

Causes damage to organs through prolonged or repeated exposure.

Label elements:

Hazard pictograms



Danger

Hazard statements May cause cancer. Route of exposure: Inhalation. Causes damage to organs through prolonged or repeated exposure.

(Cont. on page 2) USGHS

Trade name: MK 6-HY

Printing date 01/19/2023

Reviewed on 01/19/2023

(Cont. from page 1)

Precautionary statements Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Wash thoroughly after handling. In case of inadequate ventilation wear respiratory protection. Dispose of contents container in accordance with all applicable regulations.	
Wash contaminated clothing before reuse. If inhaled, get medical advice/attention if you feel unwell.	

May cause skin and eye irritation. Use personal protection equipment as required.

FOR PROFESSIONAL USE ONLY

Hazard description: NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)

HEALTH *1 Health = *10 Flammability = 0Reactivity = 0REACTIVITY 0

Other hazards

FIRE

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixture

Description: Mixture of the hazardous substance(s) listed below with additional nonhazardous ingredients.

Hazardous	components:
-----------	-------------

7778-18-9	Calcium sulfate, natural
-----------	--------------------------

14808-60-7 Quartz (SiO2)

1317-65-3 Limestone

4 First-aid measures

Description of first aid measures

General information: Get medical advice/attention if you feel unwell.

After inhalation: If breathing has stopped, give artificial respiration then oxygen if needed.

After skin contact:

Immediately wash contaminated skin with soap or mild detergent and water. If this chemical soaks clothing, immediately remove clothing and wash skin.

If skin irritation occurs, consult a doctor.

After eye contact:

Rinse cautiously with water for several minutes. If eye irritation occurs, consult a doctor.

(Cont. on page 3)

50-90%

1.0 - 2.0%

1.0-10.0%

Version Number 1.0

Trade name: MK 6-HY

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Special hazards arising from the substance or mixture No further relevant information available.

Additional information No further relevant information available.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Avoid formation of dust.

Methods and material for containment and cleaning up:

Sweep up spilled product into receptacles. Avoid formation of dust. Vacuuming or wet sweeping may be used to avoid dust dispersal.

Dispose contaminated material as waste according to section 13 of the SDS.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Avoid contact with skin.

Do not breathe dust.

Fit dust covers to mixers.

Prior to welding or cutting, Monokote must be removed from steel surfaces likely to be exposed to excessive heating. Avoid contact with eyes.

Conditions for safe storage, including any incompatibilities

Storage:

Further information about storage conditions: Store in cool, dry conditions in well sealed original receptacles.

Specific end use(s) No further relevant information available.

Page 3/9

Reviewed on 01/19/2023

(Cont. from page 2)

USGHS (Cont. on page 4)

Trade name: MK 6-HY

Reviewed on 01/19/2023

(Cont. from page 3)

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Control pa	
Components	with limit values that require monitoring at the workplace:
1317-65-3 Li	mestone
TWA (USA)	Short-term value: 10 mg/m ³ , mg/m3 ppm Long-term value: 10 mg/m ³ , mg/m3 ppm (Particulate matter no asbestos)
14808-60-7 (Quartz (SiO2)
PEL (USA)	see Quartz listing
REL (USA)	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV (USA)	Long-term value: 0.025* mg/m ³ * as respirable fraction

Additional Occupational Exposure Limit Values for possible hazards during processing: In addition to the exposure limits referenced above, the following non-specific limits for dust apply to this product; OSHA, 15 mg/m3-TWA for Total Dust and 5 mg/m3-TWA as Respirable Dust, ACGIH, 10 mg/m3-TWA as Total Dust and 3 mg/m3-TWA as Respirable Dust.

Additional information:

The lists that were valid during the creation were used as basis. Canadian employers must consult the exposure limits in their province.

Work/Hygienic Practices: The usual precautionary measures for handling chemicals should be followed.

Exposure controls

Minimize airborne dust generation. Use process enclosures, local exhaust ventilation or other engineering controls to keep airborne levels below specified exposure limits. If user operations generate dust, or mist, use ventilation to keep exposure to airborne particles below the exposure limit. Apply organizational measures, eg. by isolating personnel from dusty areas. Remove and wash soiled clothing.

Personal protective equipment:

General protective and hygienic measures:

Store protective clothing separately.

The usual precautionary measures for handling chemicals should be followed.

Breathing equipment:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Material of gloves Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Eve protection:



Safety glasses with side shield protection.

Safety glasses with side shields should be worn to prevent contact due to splashing. Under high vapor mist concentrations, tightly sealed goggles should be worn.

Body protection:

Use personal protective equipment as required.

Version Number 1.0

Trade name: MK 6-HY

Take off contaminated clothing.

9 Physical and chemical propert	9 Physical and chemical properties		
Information on basic physical and chemical properties			
General Information Appearance: Form: Color: Odor: Odor: Odor threshold:	Powder Grey Earthy Not determined.		
pH-value (~):	Not applicable.		
Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point:	Undetermined. Undetermined. Not applicable.		
Flammability (solid, gaseous):	Not determined.		
Ignition temperature:	Undetermined.		
Decomposition temperature: Auto igniting: Danger of explosion:	Not determined. Product is not self-igniting. Product does not present an explosion hazard.		
Explosion limits: Lower: Upper:	Not determined. Not determined.		
Vapor pressure: Density: (~) Relative density Vapor density Evaporation rate	Not applicable. Not determined. Not determined. Not applicable. Not applicable.		
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.		
Partition coefficient (n-octanol/water): Not determined.			
Viscosity: Dynamic: Kinematic: Molecular weight	Not applicable. Not applicable. Not determined.		
Other information	No further relevant information available.		

10 Stability and reactivity

Reactivity Stable under normal conditions.

Chemical stability

Thermal decomposition: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

No further relevant information available.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

(Cont. on page 6) USGHS

Reviewed on 01/19/2023

(Cont. from page 4)

Version Number 1.0

Trade name: MK 6-HY

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Cutting or welding may generate Sulfur dioxide.

Additional information: See section 7 for information on handling, storage and conditions to be avoided.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

1317-65-3 Limestone

Oral LD50 6450 mg/kg (rat) LC50, 96h 10.000 mg/l (fish)

Primary irritant effect:

on the skin: No irritating effect expected

on the eye: No irritating effect expected

Additional toxicological information: Prolonged exposure may cause risk of lung disease (i.e. silicosis and/or lung cancer).

Carcinogenic categories

IARC (International Agency for Research on Cancer) Human Carcinogenicity: Group 1- Positive, Group 2A- Probable, Group 2B- Possible, Group 3- Not Classifiable

14808-60-7 Quartz (SiO2)

9003-53-6 Expanded Polystyrene

NTP (National Toxicology Program)

K-Known to be carcinogenic, Ř-Máy reasonably be anticipated to be carcinogenic

14808-60-7 Quartz (SiO2)

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

Toxicity

Aquatic toxicity:

1317-65-3 Limestone

EC50, 48h 1.000 mg/l (daphnia magna) EC50, 72h 10.000 mg/l (algae)

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Not known to be hazardous to water.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Reviewed on 01/19/2023

(Cont. from page 5)

1

3

Κ

(Cont. on page 7) USGHS

Trade name: MK 6-HY

Reviewed on 01/19/2023

(Cont. from page 6)

Page 7/9

Other adverse effects No further relevant information available.

13 Disposal considerations

Disposal methods:

Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing product for disposal. Dispose of waste in accordance with all applicable regulations.

Recommendation:



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Dispose of contents/container in accordance with local/regional/national/international regulations.

4 Transport information			
UN-Number DOT, IMDG, IATA	Not applicable.		
UN proper shipping name DOT, IMDG, IATA	Not applicable.		
Transport hazard class(es)			
DOT, IMDG, IATA Class Not applicable.			
Packing group DOT, IMDG, IATA	Not applicable.		
Environmental hazards: Marine pollutant:	No		
Special precautions for user Not applicable.			
Transport/Additional information:			
DOT Remarks: Note:	Not Regulated. Not Regulated for Canada TDG.		
UN "Model Regulation":	Not applicable.		

15 Regulatory information

Other regulations in domestic and foreign countries SARA (Superfund Amendments and Reauthorization Act) Section 302/304 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):

None of the ingredients is listed.

(Cont. on page 8)

USGHS

Printing date 01/19/2023

Trade name: MK 6-HY

	(Cont. from page
North America Chemical Inventory Status	
TSCA (Toxic Substances Control Act - United States):	
All ingredients are listed or exempt from listing unless otherwise noted below.	
CEPA (Canadian DSL):	
All ingredients are listed or exempt from listing unless otherwise noted below.	
Right to Know Ingredient Disclosure:	
65996-61-4 Cellulosic Fiber	
9003-53-6 Expanded Polystyrene	
California Proposition 65: (Substances <0.1% unless noted in Section 3)	
Chemicals known to cause cancer:	
Quartz (SiO2)	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
Carcinogenicity Categories	
TLV-ACGIH (THE American Conference of Governmental Industrial Hygienists)	
Human Carcinogen - A1 Confirmed, A2 Suspected, A3 Unknown Relevance, A4 Not Classifiable	
Quartz (SiO2)	A
NIOSH-Cancer (National Institute for Occupational Safety and Health)	
14808-60-7 Quartz (SiO2)	
Volatile Organic Compounds (VOC) reported per the Emission Standards. 0 g/L	

16 Other information

The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection.

Department issuing SDS:

COLOMBIA Parquiamerica, Mamonal Km 6 Bodega 4 y 5 Manzana G Cartagena, Colombia T +57 5 6930230 | M +57 3114621174 Línea 123 - Línea de atención 24 horas CISTEMA ARL SURA 01 8000 51 1414 ó +57(1)405-5911

MEXICO Isidro Fabela s/n Col. Isidro Fabela 52600 Tianguistenco, México Mexico: (713) 690-2130 (24 hours)

BRAZIL Av. Paraná, 4690 Cajuru do Sul Sorocaba SP, Brazil 18105-000 Tel: +55 (15) 3235-4700 Fax: +55 (15) 3235-4705 Telefone para Emergência durante Transporte: Proquímica - 0800-118270

CHILE Camino El Otoño 525 Lampa, Santiago - Chile Teléfono: 56-02-4842300

(Cont. on page 9) USGHS

Reviewed on 01/19/2023

Version Number 1.0

Trade name: MK 6-HY

Fax: 56-2-4842392

ARGENTINA

Primera Junta 570 Quilmes, B1878IPL ARGENTINA Phone: 54 11-4229-5303

Contact:

The first date of preparation 08/05/2016

Number of revision times and the latest revision date 1.0 / 01/19/2023

Reviewed on 01/19/2023

(Cont. from page 8)

USGHS