

DE NEEF[®] Soil PUnE

Product Description

Soil PUnE is a hydrophobic polyurethane that, when used alone or with Soil Cat PUnE, is designed to increase the bearing capacity of permeable soil. In its uncured form, Soil PUnE is a blackish-brown nonflammable liquid. When it comes in contact with water, the grout slightly expands and, depending on temperature and amount of accelerator (Soil Cat PUnE) used, quickly cures to a very dense open cell foam that is essentially unaffected by corrosive environments and micro organisms.

Product Advantages

- Free Foam Expansion up to 3 times
- Contains no volatile solvents
- Very high strength with no creep
- Very low viscosity for permeation into tight soils
- Controlled reaction time

Product Applications

- Stabilizing soil beneath slabs and roadways
- Confinement of hazardous materials in soil
- Creating below grade cut-off curtain wall

Packaging & Handling

Soil PUnE:

5 gallon metal pail
50 gallon metal drum

Soil Cat PUnE:

25 oz. metal cans

Soil PUnE is sealed under dry nitrogen because it is sensitive to moisture, and should be stored in original containers in a dry area. Storage temperature must be between 40 °F and 90 °F. Once the packaging has been opened, the useful life of the material is greatly reduced and should be used as soon as possible.

Shelf life: 2 years.

Properties

SOIL PURE RESIN		
Solids	100%	ASTM D2369
Viscosity	50 cp at 77°F	ASTM D2196
Color	Black-brown liquid	
Density	1.12 g/cm ³	ASTM D4659
Flashpoint	284°F	ASTM D93
Corrosiveness	Non-corrosive	
Soil Cat PRe		
Viscosity	15 cp at 77°F	ASTM D2196
Color	Clear liquid	
Flashpoint	221°F	ASTM D93
Soil PRe Cured		
Density confined	1.00 g/cm ³	ASTM D3574
Compressive strength	1813 psi	confined w/sand
Flexural strength	290 psi	confined w/sand

Reaction Times

T	% CAT	END REACTION	FOAM FACTOR
40°F	0.5	14'30"	1V
	1.0	6'30"	2V
	1.5	5'00"	3V
	2.0	4'10"	3V
	2.5	2'46"	3V
50°F	0.5	12'06"	1V
	1.0	5'30"	2V
	1.5	4'30"	3V
	2.0	3'40"	3V
	2.5	2'40"	3V
60°F	0.5	11'30"	1V
	1.0	5'00"	2V
	1.5	4'00"	3V
	2.0	3'10"	3V
	2.5	2'30"	3V

68°F	0.5	10'50"	1V
	1.0	4'50"	2V
	1.5	3'50"	3V
	2.0	2'50"	3V
	2.5	2'20"	3V
77°F	0.5	8'46"	3V
	1.0	4'30"	3V
	1.5	3'25"	3V
	2.0	2'30"	3V
	2.5	2'06"	3V
86°F	0.5	8'00"	3V
	1.0	4'20"	3V
	1.5	3'05"	3V
	2.0	2'20"	3V
	2.5	2'00"	3V
95°F	0.5	7'35"	3V
	1.0	3'50"	3V
	1.5	3'05"	3V
	2.0	2'10"	3V
	2.5	1'56"	3V

Health and Safety

Always use protective clothing, gloves and goggles consistent with OSHA regulations during use. Avoid eye and skin contact. Do not ingest. Refer to Safety Data Sheet (SDS) for detailed safety precautions. SDS's can be obtained from GCP Applied Technologies or from our web site at gcpat.com. For emergencies, call CHEMTREC 1-800-424-9300.

Installation Guidelines

Warning: Consult the Technical Data Sheets and SDS before using.

Installation Instructions: For detailed installation instructions refer to the DE NEEF® technical bulletin for your application.

Catalyst: Shake catalyst can 2-3 minutes. Pour the desired amount of Soil PURE into a clean dry pail. Measure the appropriate amount of Soil Cat PURE (refer to the **Reaction Times** section of this data sheet for the desired set time) and pour it into the pail. Stir until adequately mixed.

Injection: During injection the grout will follow the path of least resistance. When the material has stopped penetrating it will continue to expand against the limits of the confined space.

Extreme conditions: For application procedures in extreme temperatures and specific environments or equipment recommendations call DE NEEF® Technical Service.

Cleaning: Clean all tools and equipment which have been in contact with the resin with DE NEEF® Washing Agent before resin has cured. Products should be disposed of according to local, state, and federal laws.

Limitations

Low temperatures will significantly affect viscosity. If site temperatures are extremely low, heat bands or heated water baths may be used on the pails before and during installation to maintain the product's temperature. Avoid splashing water into open containers, as the material is water activated. Avoid exceeding 90°F when warming.

CAUTION: pH NOTICE. Water used to activate PRe Grouts must be in the pH range of 3-10 for optimum foam quality

ca.gcpat.com | North America customer service: 1-877-4AD-MIX (1-877-423-6491)

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

DE NEEF is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2018 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Suite 475, Alpharetta, GA 30009, USA

GCP Canada, Inc., 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6.

This document is only current as of the last updated date stated below and is valid only for use in the Canada. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2024-06-21

ca.gcpat.com/solutions/products/de-neeef-waterproofing-injection-solutions/de-neeef-soil-pure