

TL-0030 — Shelf Life/Storage and Handling of GCP Waterproofing and Air Barrier Products Technical Letter

Storage Recommendation

The shelf life of GCP waterproofing and air barrier products are highly dependent on the conditions under which these products are stored. These products should be stored in their original, unopened packaging at ambient temperatures between $40^{\circ}-90^{\circ}F$ ($5^{\circ}-32^{\circ}C$). Liquid products should be protected from freezing. For specific product requirements, refer to the product data sheet and material safety data sheet.

Shelf-life Recommendation

Waterproofing products maximum shelf life:

- All BITUTHENE[®] Waterproofing Membranes 12 months
- BITUTHENE[®] Liquid Membrane 18 months
- BITUTHENE[®] Deck Prep 18 months
- BITUTHENE[®] Mastic 12 months
- BITUTHENE[®] Primer WP 3000 12 months
- BITUTHENE[®] Adhesive Primer B2 LVC 18 months
- PREPRUFE[®] 300R/160R Waterproofing Membrane 18 months
- PREPRUFE[®] 250 Waterproofing Membrane 18 months
- All PREPRUFE[®] Plus Membranes 12 months
- All PREPRUFE[®] 275 Membranes 12 months
- All PREPRUFE[®] 800PA waterproofing Membranes 24 months
- All PREPRUFE[®] Tapes 18 months
- All PREPRUFE[®] Detail Tapes 18 months
- PREPRUFE[®] SCS Grouts 6 months
- PREPRUFE[®] SCS Grouts Activators 12 months
- PREPRUFE[®] SCS Membrane 12 months
- PREPRUFE[®] SCS ancillaries 24 months
- PREPRUFE[®] EG 75 grouts 24 months
- PREPRUFE[®] Tieback Covers 12 months
- FLORPRUFE[®] 120 Vapor Barrier 18 months
- ADCOR[®] 500S Hydrophilic Waterstop 120 months
- ADCOR[®] 500S Adhesive 12 monthss



- SWELLSEAL[®] 2010 TPR 120 months
- SWELLSEAL[®] Sealant WA 12 months
- All HYDRODUCT[®] Drainage Composites and Accessories 24 months

Liquid waterproofing products maximum shelf life:

- All PROCOR[®] Fluid Applied Waterproofing 12 months
- PROCOR[®] Reinforcement Mesh 36 months
- PROCOR[®] Composite Membrane 12 months
- SILCOR[®] 900HA and SILCOR[®] 900MP 12 months
- SILCOR[®] Primer EPF Kit and SILCOR[®] Fast Set Primer Kit 24 months

INJECTO products maximum shelf life:

- All INJECTO[®] Kit components 24 months
- DeNeef[®] INJECTO[®] PURe 24 months
- DeNeef[®] Flex Cat PURe 24 months
- Washing Agent 12 months

PERM-A-BARRIER[®]air barrier products maximum shelf life:

- All PERM-A-BARRIER[®] Wall Membranes and Aluminum Wall Membranes 12 months
- PERM-A-BARRIER[®] Wall Flashing, Detail Membrane and Aluminum Flashing 12 months
- PERM-A-BARRIER[®] VPS 30 24 months
- PERM-A-BARRIER[®] NPS and NPS Detail Membrane 24 months
- PERM-A-BARRIER[®] VPL and VPL Low Temp 12 months
- PERM-A-BARRIER[®] VPL 50RS UV Stable 18 months
- PERM-A-BARRIER[®] NPL 10 and NPL 10 LT 12 months
- PERM-A-BARRIER[®] S100 sealant 15 months
- PERM-A-BARRIER[®] Universal Flashing & Sealant 12 months
- PERM-A-BARRIER[®] WB Primer 12 months
- PERM-A-BARRIER[®] Adhesive Primer 18 months

Products will remain stable when stored under recommended storage conditions. Products will not be extended beyond the shelf-life date. For further information contact your local GCP representative.

North America customer service: 1-877-4AD-MIX (1-877-423-6491)

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Suite 450, Alpharetta, GA 30009, USA

GCP Canada, Inc., 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6.

This document is only current as of the last updated date stated below and is valid only for use in the Canada. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.